




Terminal ilhós (pino tubular) simples isolado Punteras tubulares simples aisladas Insulated ferrules



Material: Cobre, estanhado eletroliticamente.

- Isolamento de NYLON com retardamento de chama.
- Temperatura de trabalho: -55°C +105°C.
- Tensão acima de 1000 volts.

Material: Cobre, estañado electroliticamente.

- Aislamiento de NYLON con retardo de llama.
- Temperatura de trabajo: -55°C +105°C.
- Tensión superior a 1000 voltios.

Material: Copper, electrolytically tinned.

- Insulation of NYLON with flame retardancy.
- Working temperature: -55°C +105°C.
- Voltage above 1000 volts.

Bitola Sección Wire Size mm ²	Código Crimper	Norma Standard	S		Código Crimper	Norma Din	L	
			mm	mm			mm	mm
0,25	CT3602	violeta	6,0	10,0				
	CT3602-L		8,0	12,0				
0,34	CT3603	turqueza	6,0	12,0				
	CT3604-L		10,0	16,0				
0,5	CT3604	branco	8,0	14,0	CT3804	branco	8,0	14,0
	CT3605-L		10,0	16,0	CT3804-L		10,0	16,0
0,75	CT3605	azul	8,0	14,0	CT3805	cinza	8,0	14,0
	CT3605-L		10,0	16,0	CT3805-L		10,0	16,0
1	CT3606	vermelho	8,0	14,0	CT3806	vermelho	8,0	14,0
	CT3606-L		10,0	16,0	CT3806-L		10,0	16,0
1,5	CT3607	preto	10,0	16,0	CT3807	preto	8,0	14,0
	CT3607-L		12,0	18,0	CT3807-L		12,0	18,0
2,5	CT3608	cinza	10,0	16,0	CT3808	azul	8,0	14,0
	CT3608-L		12,0	18,0	CT3808-L		12,0	18,0
4	CT3609	laranja	12,0	20,0	CT3809	cinza	10,0	17,0
	CT3609-L		18,0	26,0	CT3809-L		18,0	26,0
6	CT3610	verde	12,0	20,0	CT3810	amarelo	12,0	20,0
	CT3610-L		18,0	26,0	CT3810-L		18,0	26,0
10	CT3611	vermelho	18,0	28,0	CT3811	vermelho	12,0	22,0
	CT3611-L		22,0	31,0	CT3811-L		22,0	31,0
16	CT3612	azul	18,0	28,0	CT3812	azul	12,0	24,0
	CT3612-L		22,0	32,0	CT3812-L		22,0	32,0
25	CT3613	amarelo	18,0	28,0	CT3813	amarelo	16,0	29,0
	CT3613-L		22,0	35,0	CT3813-L		22,0	35,0
35	CT3614	vermelho	18,0	32,0	CT3814	vermelho	16,0	30,0
	CT3614-L		25,0	39,0	CT3814-L		25,0	39,0
50	CT3615	azul	25,0	40,0	CT3815	azul	20,0	36,0
70	CT3616	amarelo	21,0	37,0	CT3816	amarelo	21,0	37,0
95	CT3617	vermelho	25,0	44,0	CT3817	vermelho	25,0	44,0
120	CT3618	azul	27,0	48,0	CT3818	azul	27,0	48,0
150	CT3619	amarelo	32,0	58,0	CT3819	amarelo	32,0	58,0